

# Rack mount rugged military monitor

## 29LR(inch)D35MP-M Series

### Highlights :

- ✓ Rugged for military applications
- ✓ Contrast enhancing AR safety glass
- ✓ High brightness
- ✓ VGA-UXGA, PAL/NTSC
- ✓ 19" standard rack mounting
- ✓ IP65 minimum



### TECHNICAL SPECIFICATIONS


Active display area	<input type="checkbox"/> 15" <input type="checkbox"/> 17" <input type="checkbox"/> 19" <input type="checkbox"/> 20.1" <input type="checkbox"/> 21.3" <input type="checkbox"/> 23.1"
Mounting	19" standard rack 6U to 9U
Native resolution	<input type="checkbox"/> 1024 x 768 <input type="checkbox"/> 1280 x 1024 <input type="checkbox"/> 1600 x 1200
Ratio	4:3
Inputs connectors	8STO-12G35SN, 851-02R123P50
Signal sync	Separate H&V, Composite
RGB Signal	Analog RGB 0.7-1Vp-p
Sync range	Horizontal: 15kHz(CVBS) else 31kHz - 91kHz Vertical: 56-85Hz
Contrast Ratio	800:1 typical
Brightness	280 cd/m <sup>2</sup> typical
OSD	Front
No. Colors	16.7M
Power Supply	15-30V DC
Environment	Operating temp: 0-15°C ~ 55°C Storage temp: -20°C ~ 60°C EMC: MIL-STD – 461E
Dimensions	Depending on screen size (contact us for more precisions)
Housing	Aluminium
Shock and Vibration	MIL-STD-810F
Options	<input type="checkbox"/> Touchscreen resistive / capacitive

# Rack mount rugged military monitor

## 29LR(inch)D35MP-M Series

### DRAWINGS

FRONT VIEW



SIDE VIEW



REAR VIEW

