

# Low frequency LCD desktop monitor

## LCDXXADKL-Series

### Highlights :

- ✓ For all slow scan signals
- ✓ 15 to 19-inch TFT LCD
- ✓ 5x BNC and DB9 input
- ✓ Protective toughened glass
- ✓ Metal casing
- ✓ Desktop version
- ✓ 1x 5-key OSD on front



### TECHNICAL SPECIFICATIONS

Display Area	15" TFT LCD	17" TFT LCD	19" TFT LCD
<b>Mounting</b>	Desktop, support VESA	Desktop, support VESA	Desktop, support VESA
<b>Glass</b>	Protective toughened glass	Protective toughened glass	Protective toughened glass
<b>Native Resolution</b>	1024 x 768	1280 x 1024	1280 x 1024
<b>Ratio</b>	4:3	4:3	4:3
<b>Input</b>	5x BNC, DB9	5x BNC, DB9	5x BNC, DB9
<b>Signals</b>	MDA, CGA, EGA, RGB, RGB Sog, RGBS, RGBHV, YPbPr	MDA, CGA, EGA, RGB, RGB Sog, RGBS, RGBHV, YPbPr	MDA, CGA, EGA, RGB, RGB Sog, RGBS, RGBHV, YPbPr
<b>Sync range</b>	Horizontal: 12-60kHz Vertical: 40-100Hz	Horizontal: 12-60kHz Vertical: 40-100Hz	Horizontal: 12-60kHz Vertical: 40-100Hz
<b>OSD</b>	Front side 5-key	Front side 5-key	Front side 5-key
<b>Contrast Ratio</b>	1000:1 typical	1000:1 typical	1000:1 typical
<b>Brightness</b>	250cd/m <sup>2</sup> typical	250cd/m <sup>2</sup> typical	250cd/m <sup>2</sup> typical
<b>Backlight</b>	LED	LED	LED
<b>No. colours</b>	16.2M	16.7M	16.7M
<b>Power Supply</b>	+12V DC External Power Adapter: 100 ~ 250VAC, 50/60Hz	+12V DC External Power Adapter: 100 ~ 250VAC, 50/60Hz	+12V DC External Power Adapter: 100 ~ 250VAC, 50/60Hz
<b>Environmental</b>	Operating Temp: 0°C ~ 40°C Relative Humidity: 10% ~ 90%	Operating Temp: 0°C ~ 40°C Relative Humidity: 10% ~ 90%	Operating Temp: 0°C ~ 40°C Relative Humidity: 10% ~ 90%
<b>Dimensions</b>	380.0(W) x 359.0(H) x 155.0(D) mm (w/o base)	409.4(W) x 398.2(H) x 175.0 (D) mm (w/o base)	445.4(W) x 420.2(H) x 175.0(D) mm (w/o base)
<b>Housing</b>	Metal	Metal	Metal

<b>Options</b>	<input type="checkbox"/> Touchscreen <i>Other mounting available on other series (Head, Rackmount, Panelmount...).</i>
----------------	---------------------------------------------------------------------------------------------------------------------------