



ThermoView® TV40

Thermal Imager Datasheet

Highlights

- Wide temperature range: -10 to 1200 °C (14 to 2192 °F)
- 320 x240 and 640 x 480 infrared resolution
- 9 or 60 Hz models available
- Rugged housing, IP67 (NEMA 4) rated
- Sighting: IR-Fusion[®] technology (thermal and visible sighting) for easy alignment and added detail on blended images
- Remote motorized focus
- Multiple field interchangeable lens options available
- GigE Vision interface
- LAN/Ethernet with PoE for communication with the thermal imager provides access to Ethernet, Web server and ThermoView Software
- ThermoView software for industrial automation applications
- Ambient temperatures to 200 °C (392 °F) with high temperature enclosure
- Air purge and accessories available



New to the world – a high performance industrial thermal imager from the brand you trust, backed by 150 years of industrial application experience. Designed for the most challenging environmental conditions you face, and supported by an intuitive and powerful analysis software, ThermoView TV40 provides the performance and personalization to meet your process monitoring and control needs.

Lens Type	Distance		HFOV		VFOV		Pixel Size	
	m	ft.	m	ft.	m	ft.	mm	in.
	0.5	1.6	0.3	1.0	0.2	0.8	0.93	0.037
Standard Lens	1.0	3.3	0.6	2.0	0.5	1.5	1.85	0.073
	3.0	9.8	1.8	6.0	1.4	4.5	5.56	0.219
	10.0	32.8	6.1	20.1	4.6	15.1	18.54	0.730
	0.5	1.6	0.4	1.4	0.3	1.0	1.23	0.048
Wide Angle	1.0	3.3	0.8	2.7	0.6	2.0	2.45	0.097
FPI 0.75X WIDE LENS	3.0	9.8	2.5	8.2	1.8	6.0	7.36	0.290
	10.0	32.8	8.3	27.2	6.1	20.1	24.54	0.966

Lens Field of View examples



HFOV – Horizontal Field of View (horizontal aperture angle) VFOV – Vertical Field of View (vertical aperture angle)

Measuring field sizes can be calculated online at: www.flukeprocessinstruments.com/TV40



Measurement Specifications

	ThermoView TV43	ThermoView TV46			
Sighting	Thermal Imager + Visible Light Camera (640 x 480)				
Measuring Range	-10 to 1200 °C (14 to 2192 °F) Subrange 1: -10 to 80 °C (14 to 176 °F) Subrange 2: -10 to 250 °C (14 to 482 °F)				
Measurement Accuracy	±2 °C or ±2	o (reading)			
Infrared Resolution	320 x 240 (76,800 pixels)	640 x 480 (307,200 pixels)			
Spectral Range	8 - 1	4 µm			
Detector	Uncooled focal plane array				
Field of View	Horizontal 34° x 25.5°				
Add on Lens Options (add in field)	0.75x Wide le 2x lens (1 4x lens (1 Macro	ns (45° x 34°) 7° x 12.7°) 3.5° x 6°) 9 lens			
Focus Range	IR 15 cm – ∞ (motorized remote focus) Visible light: 60 cm – ∞				
Thermal Imager Frame Time	9 or 60 frames/sec. (must be specified at the time of ordering)				
Emissivity Correction	0.10 to 1.00				
Interface	GigE Vision				
LED Display	Power supply indication, system error codes				
Operating Temperature	-10 to 50 °C (14 to 122 °F)				
Storage Temperature	-20 to 50 °C (-4 to 122 °F)				
Humidity	10 – 95% non-condensing				
Power Supply	DC + 12 to 26 V, PoE (Power over Ethernet)				
Power Consumption	8 W (typical) 13 W (maximum)				
Shock Resistance	IEC 60068-2-27 (mechanical shock): 50 g, 6 ms, 3 axis				
Vibration Resistance	IEC 60068-2-26 (sinusoidal vibration): 3 g, 11 – 200 Hz, 3 axis				
Environmental Protection	IP67 (NEMA 4)				
Dimensions (W x H x L)	Approximately 83 x 83 x 158 mm (3.25 x 3.25 x 6.22")				
Weight	Approximately 1.08 kg (2.38 lbs)				

Thermal Imager rear view

Thermal Imager front view





Thermal Imager Dimensions





Accessories

TV40 thermal imagers are shipped with manual, calibration certification, quick reference guide, safety sheet.

Additional accessories include but are not limited to:

- Wide Angle for TV43/TV46 (45° x 34°) (FPI 0.75X WIDE LENS)
- 2x telephoto for TV43/TV46 (17° x 12.7°) (FPI 2X LENS)
- 4x telephoto for TV43/TV46 (8.5° x 6°) (FPI 4X LENS)
- Macro Lens for TV43/TV46 (FPI MACRO LENS)

- PoE Injector (industrial duty) provides power and also acts as a single Ethernet hub (110/220 VAC input) (A-TV-POE-2)
- Air purge collar (includes protective window) (A-TV-AP)
- Protective enclosure (water cooled/air purged) (A-TV-WC)
- Protective Window ThermoView (A-TV-PW)
- 24 VDC 1.2 A industrial power supply, DIN rail mount (A-PS-DIN-24V)
- Mounting Base (A-TV-MB)

The Fluke Process Instruments Guarantee

The ThermoView TV40 thermal imager is supported by a 2 year warranty. With a network of trained representatives and agents in over one hundred countries and offices located in the U.S., Germany and China, we provide local service and support.

Tel : +33 (0) 472 370 470



info@altronics.fr www.altronics.fr