

# KVMA20HR



## **Features**

### Key features:-

- 1U 20" LCD console drawer
- Ultra high resolution 1600 x 1200
- 104-key keyboard with touchpad
- Enhanced aesthetics with moulded front handle and two point lock

# Left Side View Front View Front View Top View Top View Unit: mm





# KVMA20HR

The information is believed to be accurate. However Amplicon Liveline Limited accepts no responsibility for any problems caused by errors and omissions. Specifications are subject to change without notice.

## **Specifications**

| LCD Panel                 | Size (diagonal): 20.4" TFT Max resolution: 1600 x 1200 Brightness (cd/m²): 300 Backlight: CCFL Colours: 16.7 M Contrast ratio (typ): 800 : 1 Viewing angle (H/V): 178° x 178° Active area (mm): 408 x 306 MTBF (hrs): 45,000 Signal input: VGA | Regulatory  | Safety: FCC & CE certified<br>Environmental: RoHS2 & REACH compliant                                       |
|---------------------------|--|---|--|
|                           |  | Power   | Input: Auto-sensing 100 to 240VAC, 50 / 60Hz<br>Consumption: Max. 48 Watt, Standby 5 Watt                  |
|                           |  | Environmental  Operating: 0 to 50°C Storage: -5 to 60°C Relative humidity: 5–90%, non-condensing Shock: 10G acceleration (11ms duration) Vibration: 5~500Hz 1G RMS random vibration | Storage: -5 to 60°C<br>Relative humidity: 5~90%, non-condensing<br>Shock: 10G acceleration (11ms duration) |
| Casing Colour             | Black (RAL 9005)   |   |  |
| Weight                    | Net: 14.5kgs (31.9lbs)<br>Gross: 22kgs (48.4lbs)   |   |  |
| Dimensions<br>(W x D x H) | Product: 439.6 x 650 x 44 mm (17.3 x 25.6 x 1.73 in)<br>Packing: 595 x 860 x 140 mm (23.4 x 33.9 x 5.5 in)   |   |  |

